

## GENERAL INFORMATION

X-Tra Power is a soil, in furrow, foliar or irrigation applied micronutrient and is non-phytotoxic when used as directed.

## DIRECTIONS FOR USE

It is a violation of law to use this product inconsistent with its labeling.

## RECOMMENDED USES

### FOR IN-FURROW APPLICATION:

Apply X-Tra Power at 0.5 to 2 quarts per acre in 5 gallons of solution per acre and apply in seed furrow at planting.

### FOR TRANSPLANT APPLICATION:

Mix 2 to 5 pints into sufficient transplant water to transplant 1 acre of crop. Add X-Tra Power to transplant solution at a rate of 5% of total solution or about 6.5 ounces X-Tra Power into 1 gallon of water.

### FOR IRRIGATION/SOIL DRENCH APPLICATION:

Prepare a tank mix solution to inject 32 to 48 fl. oz. per acre into the irrigation system. Apply X-Tra Power near the end of the watering cycle. Apply every 7 to 14 days through the irrigation system in addition to the normal N-P-K fertility program.

### FOR FOLIAR SPRAY APPLICATION:

**Field Crops:** For use on all field crops including but not limited to: Alfalfa, barley, canola, corn, cotton, flax, milo, oats, soybeans, sugar beets, sugar cane, wheat. Apply 0.5 to 1 quart per acre (1.2 to 2.4 liters per hectare) per application.

**Vegetables and Fruits:** For application on all vegetable and fruit crops including but not limited to: All beans, broccoli, cabbage, cauliflower, carrots, celery, lettuce, melons, onions, peppers, potatoes, peanuts, sweet corn, spinach, strawberries, tomatoes, turnips, watermelons. Apply 0.5 to 1 quart per acre (1.2-2.4 liters per hectare) per application.

**Tree and Vine Crops:** For use on all tree and vine crops including but not limited to: Almonds, apples, avocados, citrus, grapes, nectarines, pears, peaches, pecans, plums, walnuts. Apply 1 quart of X-Tra Power in 100 gallons of water.

▶ Do not exceed two quarts per acre per application for foliar sprays.

Foliar apply X-Tra Power in minimum of 20 gallons of water per acre (180 liters per hectare) through conventional equipment or 5 gallons of water per acre (45 liters per hectare) when using ultra low volume equipment.

**MIXING INSTRUCTION:** Follow this mixing order 1. Water 2. X-Tra Power 3. Pesticide.

X-Tra Power will disperse in water with little agitation. X-Tra Power is compatible with most fertilizers and pesticides. Always conduct a jar test when using new or untried combinations. The addition of 0.5% (total solution) of nitrogen solution, ammonium sulfate, or low biuret urea may aid leaf absorption.

Notice: The information contained herein is true and accurate to the best of our knowledge and belief, but is presented without guarantee since field conditions and use are beyond our control. Neither the manufacturer nor the seller make any warranty, expressed or implied concerning the use of this product other than indicated on the label. Buyer assumes all risk of use of this material when such use is contrary to label instruction. Read and follow the label directions carefully.

CONDITIONS OF SALE: 1. Seller warrants that this product consists of the ingredients specified and is reasonably fit for the purpose stated on this label when used in accordance with directions under normal conditions of use. No one, other than an officer of Seller, is authorized to make any warranty, guarantee of direction concerning this product. 2. Because of time, place, rate of application and other conditions of use are beyond sellers control, Sellers liability from handling, storage and use of this product is limited to replacement of product or refund of purchase price.

# X-Tra Power

2-0-0

## GUARANTEED ANALYSIS

Total Nitrogen (N) .....	2.0%
2% Water Soluble Nitrogen	
Magnesium (Mg).....	0.8%
0.8% Chelated Magnesium	
Copper (Cu).....	0.8%
0.8% Chelated Copper	
Manganese (Mn).....	0.8%
0.8% Chelated Manganese	
Zinc (Zn).....	3.2%
3.2% Chelated Zinc	

Derived from Magnesium MEA, Copper MEA, Manganese MEA, Zinc MEA

## CAUTION

**KEEP OUT OF REACH OF CHILDREN; MAY BE HARMFUL IF SWALLOWED, INHALED OR IN CONTACT WITH SKIN; MAY CAUSE EYE IRRITATION. MAY CAUSE DAMAGE THROUGH PROLONGED EXPOSURE.**

PRECAUTIONS: Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in well-ventilated area. Avoid release to environment. Wear protective gloves/protective clothing/eye protection/face protection. Keep container tightly closed. Keep cool and protected from sunlight.

If medical advice is needed, have product container or label at hand. For more details regarding the safe use/handling, storage and disposal of this product as well as additional hazards and first aid measures, please obtain the current Safety Data Sheet at [www.stollerusa.com](http://www.stollerusa.com).

## STORAGE AND DISPOSAL

We recommend storing pails a maximum of three pails high. Do not stack pallets. Store container tightly closed in a cool/well-ventilated dry place protected from sunlight above 40°F. Do not allow container to freeze. Store locked up. DISPOSE of contents/container at a permitted facility or as advised by your local regulatory authority. Do not contaminate water, food or feed by storage or disposal. Do not apply directly to areas where surface water is present, or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment wash water. Do not reuse empty container.

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.html>

# X-Tra Power®

## 2-0-0

US Patent: 5,997,600  
F2399

Density: 10.3 lb/gal (1.23 kg/L) @ 68°F (20°C)

### NET CONTENT

- 2.50 gal (9.5 L)
- 2.64 gal (10.0 L)
- 5.00 gal (18.9 L)
- 5.28 gal (20.0 L)
- 55.00 gal (208.2 L)
- 275.00 gal (1041.0 L)
- BULK

### NET WEIGHT

- 25.8 lb (11.7 kg)
- 27.2 lb (12.4 kg)
- 51.5 lb (23.4 kg)
- 54.4 lb (24.7 kg)
- 566.5 lb (257.3 kg)
- 2832.5 lb (1286.7 kg)

Z- XTP

Rev: 20180904

Manufactured and Guaranteed by  
Stoller Enterprises, Inc.

9090 Katy Freeway, Suite 400  
Houston, TX 77024  
Phone: 1-800-539-5283 or 713-461-1493

